Docket No.: 22193-00026-US1

This listing of the claims replaces all listings and prior versions of the claims in this application.

<u>Listing of the Claims</u>:

1. (Currently amended) A method of transforming energy in a rotary screw machine (Fig. 1a), which comprises:

a first set of conjugated male and female elements; (5, 6, 7; 15, 16, 17) and

at least a second set of conjugated male and female elements (8, 9; 5', 6', 7'; 15', 16', 17'), spaced apart from said first set (1) along a central axis of said machine, wherein said female elements (5, 6, 15, 16; 8; 5', 6', 15', 16') of each set have having an inner profiled surface (105, 106, 115, 116; 108; 105', 106', 115', 116') centered about a first longitudinal axis, (Z) and—wherein said male elements (6, 7, 16, 17; 9; 6', 7', 16', 17') of each set (1, 2, 3) have having an outer profiled surface (206, 207, 216, 217; 209; 206', 207', 216', 217') centred centered about a second longitudinal axis, [[-]] said first axis and said second axis being parallel to each other, and [[-]] said male elements being placed in a cavity of the corresponding female elements; [[,]]

said method comprising:

wherein performing an axial movement with working chambers that are formed between the female and/or male elements upon rotary motion of the male and/or female elements; working chambers which are formed between the female and male elements perform an axial movement, and

wherein synchronizing the rotary motions of the different sets (1, 2, 3) are synchronized in such a manner that synchronous and in-phase motion of the elements in different sets (1, 2, 3) is performed with different values of angular periods of oscillation of axial movement of said working chambers.

- 2. (Original) The method of claim 1, wherein the angular period decreases from one set to the next set, thereby having the working medium compressed.
- 3. (Original) The method of claim 1, wherein the angular period increases from one set to the next set, thereby having the working medium expanded.
- 4. (Currently amended) The method of any of the proceeding claims claim 1, using a hollow shaft (4) and the working medium passing therethrough as a means for synchronizing the rotary motions of the different sets (1, 2, 3).
- 5. (Currently amended) The method of any of the proceeding claims claim 1, wherein:

a first set (1) forms a differential kinematic mechanism having three degrees of freedom of a mechanical rotation of which two degrees of freedom are independent;[[,]] and

wherein a second set (2) forms a planetary kinematic mechanism, having two degrees of freedom of a mechanical rotation, of which one degree of freedom is independent.

- 6. (Currently amended) The method of any of the proceeding claims claim 1, wherein thermal energy of the working medium is removed and supplied in a heat exchanger.
- 7. (Currently amended) The method of any of the proceeding claims claim 1, wherein mechanical energy produced in one of said sets is used to drive another device.
- 8. (New) The method of claim 2, using a hollow shaft and the working medium passing therethrough as a means for synchronizing the rotary motions of the different sets.

Docket No.: 22193-00026-US1

10. (New) The method of claim 2, wherein:

a first set forms a differential kinematic mechanism having three degrees of freedom of a mechanical rotation of which two degrees of freedom are independent; and

a second set forms a planetary kinematic mechanism, having two degrees of freedom of a mechanical rotation, of which one degree of freedom is independent.

11. (New) The method of claim 3, wherein:

a first set forms a differential kinematic mechanism having three degrees of freedom of a mechanical rotation of which two degrees of freedom are independent; and

a second set forms a planetary kinematic mechanism, having two degrees of freedom of a mechanical rotation, of which one degree of freedom is independent.

12. (New) The method of claim 4, wherein:

a first set forms a differential kinematic mechanism having three degrees of freedom of a mechanical rotation of which two degrees of freedom are independent; and

a second set forms a planetary kinematic mechanism, having two degrees of freedom of a mechanical rotation, of which one degree of freedom is independent.

- 13. (New) The method of claim 2, wherein thermal energy of the working medium is removed and supplied in a heat exchanger.
- 14. (New) The method of claim 3, wherein thermal energy of the working medium is removed and supplied in a heat exchanger.
- 15. (New) The method of claim 4, wherein thermal energy of the working medium is removed and supplied in a heat exchanger.

- 16. (New) The method of claim 5, wherein thermal energy of the working medium is removed and supplied in a heat exchanger.
- 17. (New) The method of claim 2, wherein mechanical energy produced in one of said sets is used to drive another device.
- 18. (New) The method of claim 3, wherein mechanical energy produced in one of said sets is used to drive another device.
- 19. (New) The method of claim 4, wherein mechanical energy produced in one of said sets is used to drive another device.
- 20. (New) The method of claim 5, wherein mechanical energy produced in one of said sets is used to drive another device.

REMARKS

Claims 1-20 are pending in the application. Claims 1 and 4-7 have been amended to avoid multiple dependencies, to correct minor typographical errors and to improve readability. Claims 8-20 are new and include subject matter from the original multiple dependent claims. No new matter is presented. Each claim is now identified by its proper status.